



CMP SERIES

DOUBLE MASTS AERIAL WORK PLATFORM

Standard Features


- Aluminum platform basket
- Polyurethane non-mark tires
- Forklift pockets
- Foldable inclined ladder
- Two controls of the platform and base
- Lower beeper warning
- Reversal platform
- Lowering switch
- Outrigger storage frame

Options Features

- Door type wide platform
- Extendable platform
- Narrow/Rough ground chassis
- Wide chassis
- DC power
- Tool box
- Platform positioning laser lights
- Fluorescent tubes box
- Working flashing beacon
- Top limit protection auto-stop device
- Auxiliary drive wheel
- Maintenance-free battery
- Equipment protection cover



CMP Working Range



Model	CMP-10	CMP-12	CMP-14	CMP-16	CMP-18
Standard Parameter					
Working height (m)	10	12	14	16	18
Platform height (m)	8	10	12	14	16
Lift capacity (kg)	272	272	200	200	150
Weight (kg)	800	850	900	1065	1185
Stowed size (m)(A*B*C)	1.48×0.8×1.98		1.6×0.8×1.98	1.75×0.81×2.36	2×0.8×2.75
Platform size (m)(D*E*H)	1.37×0.7×1.1		1.5×0.7×1.1	1.46×0.6×1.1	1.8×0.7×1.1
Outrigger footprint (m)(F*G)	1.9*2.1		2.5*2.1	2.7*2.8	2.7*2.8
Power source(AC/DC)	220V/110V/12V				
Option wide chassis parameter					
Stowed size (m)(A*B*C)	2.02×0.8×2		2.02×0.8×2.75	-----	
Platform size (m)(D*E*H)	1.63×0.8×1.1		1.8×0.7×1.1	-----	
Outrigger footprint (m)(F*G)	1.8×3.0		2.7×2.8	-----	
Weight (kg)	885	935	985	-----	-----
Option rotate chassis parameter					
Stowed size (m)(A*B*C)	-----				2.7×0.85×1.98
Platform size (m)(D*E*H)	-----				1.49×0.78× 1.1
Outrigger footprint (m)(F*G)	-----				2.98×2.81
Weight (kg)	-----				1540

CMP Collecting Chart

